

Digi-Cling Printable Film is an excellent choice for graphic applications that require repositionability and removability. Digi-Cling features a print-receptive OPP surface that offers outstanding print performance on a wide variety of processes including offset, screen, letterpress, and flexography. This printable film provides excellent dimensional stability and will not shrink or curl like similar printable media products, even with heavy ink coverage. Digi-Cling also includes advanced microsphere adhesives that allows for easy removal from walls and interior windows without damage or leaving adhesive residue behind.

- Print directly to the the OPP Film
- Removable/repositionable adhesive backing
- Features advanced microsphere adhesive technology
- Heavy duty 90# lay flat liner for easy converting and transporting.

Film Characteristics

Thickness:	4 mil
Release Liner:	90# Claycoated Paper
pH Film:	7
Adhesive Type:	Repositionable Microsphere
Core Size:	3"
Winding:	Adhesive In

Recommendations

- 1) For use in indoor applications. The microsphere adhesive is removable up to 12 months after applications.
- 2) Allow the printed media to fully dry. Wait at least 24 - 48 hours before cutting or applying to walls.
- 3) Apply to a smooth, clean surface such as a painted wall or interior window. Do not apply directly to bare drywall, textured wallpaper, porous surfaces, or walls that have been painted within the last 30 days. For the best result, apply with a squeegee to remove any trapped air pockets.
- 4) Wash the wall or surface thoroughly with soap and water before applying graphic. If heavy cleaners are required, take care to rinse off all leftover detergent residue before application. The presence of dust and other particles may adversely affect product adhesion.



Printer Compatability:

- UV Cured Inkjet
- Offset
- Screen
- Letterpress
- Flexography

Digi-Cling

Part Number	Roll Size
DC25025	25" x 25'
DC54100	54" x 100'
DC54200	54" x 200'

