





The System 2760 DN is ideal for any organization that wants to bring high-quality finishing in-house. The System 2760 is comprised of an automatic feeder, one-sided laminator, an automatic sheet separator and jogger. The laminator features two sets of heated nip rollers in order to provide enhanced adhesion to even the most difficult digital prints.



Dual Heated Nip Rollers



Automatic Sheet Feeder

Optional Release Liner Takeup
for Pressure Sensitive FilmsTouch Screen
Controls**Made in the USA**

- ☐ Designed for today's on demand digital print, short run jobs.
- ☐ Can handle sheets from 8 1/2" x 11" up to 26" wide by 30" long at speeds up to 60 fpm.
- ☐ Curl management system places film on the paper in a relaxed manner for a flat finished product.
- ☐ Features touch pad controls and a swing out mandrel for quick film changeovers.
- ☐ Dual heated nip rollers offer enhanced adhesion to digital prints of all types.
- ☐ Easy feed loader allows load access from the top, side or back of the feeder, making job change overs a snap.
- ☐ Pressure sensitive release liner rewind option for processing PSA (cold) films at high speeds.

The above information is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. All material should be tested by purchaser to determine final suitability.

Technical Specifications


Dimensions:	5'W x 14½'L x 5'H	(152.4cm x 442cm x 152.4m)
Electrical:	220 Volt 30 amp single phase	220 Volt 30 A 1 phase
Air:	6 cfm	(1.6 m³/m)
Warmup Time:	20 Minutes	20 Minutes
Temp. Range:	180°F - 300°F	(70°C - 140°C)
Speed:	Up to 60 fpm	(18m/minute)
Min. Sheet Size:	8 ½" x 11"	(21.6cm x 27.9cm)
Max Sheet Size:	26" x 30"	(66cm x 76.2cm)
Min Sheet Thickness:	80 lb. Text	115g/m²
Max Sheet Thickness:	18 pt. Board	350g/m²

Available Options

Embossed Roller (for Linen Textures, etc.)

Release Liner Takeup for Pressure Sensitive Products

Foot Print



Feeder

This state-of-the-art feeder and belt table aligns sheets for accurate registration and processing. The System 2760 is equipped to handle a wide range of stocks from letter size up to 26" x 30". An extended feeder option is also available to process sheets up to 40" long.

Laminator

The laminator provides accurate heat and nip pressure controls, perfect for even the toughest offset and digital prints. A patented curl management system places the film on the paper in a relaxed manner for a flat, finished product. The main roller can also be easily switched out with an embossed roller option for textured finishes. Laminating films and adhesives are easily loaded onto a swinging supply mandrel that is equipped with sideways adjustments and centering marks. A pressure sensitive rewind option also offers the ability to run pressure sensitive (cold) adhesive products.

Cutter

The cutter offers complete sheet separation without bursting. Physically cutting sheets with a blade instead of bursting offers the ability to process films thicker than 1.3 mil. The cutter is also compatible with polyester films and will not result in frayed edges that make stacking and registering sheets difficult.

Visit www.dkgroup.com for videos and more information on the System 2760

D&K Group Inc.
1795 Commerce Drive
Elk Grove Village, IL, 60007

P: 800.632.2314
F: 847.956.8214
www.dkgroup.com

