



EXPRESSION® Finish Guard™ UV Laminating Films

Add the right finish and protect your mounting and framing projects with Expression® Finish Guard™ UV Laminating Films, the artful solution. All the Finish Guard™ finishes offer a durable and lightweight alternative to glass and will safeguard your work for a lifetime.

Laminating Film Features

- Durable, lightweight alternative to glass
- Special UV inhibitors help reduce damage from sunlight and florescent lighting
- Easy to use, with a clear, low-tack adhesive coating on one side
- All rolls are pierced

Finish Guard™ Laminating Films have four distinct finishes, offering a variety of creative options

Finish Guard™ Gloss - a clear, glossy film that brings out the brightest colors of your finished piece.

Finish Guard™ Suede - a textured finish that reduces glare and produces a soft, suede appearance.

Finish Guard™ Satin Matte - soft, moderately-reflective finish that enhances colors while reducing glare for clear, easy viewing.

Finish Guard™ Canvas - a distinctive canvas-like texture and soft sheen add surface interest to portraits, landscapes and reproductions.





Expression Framing Products
D&K Group, Inc.
206 Cooper Street, Suite 111
Statesville, NC 28677

Customer Service: 888-240-6021
Technical Service: 888-240-6021
Fax: 704-990-2204
Hrs: 8:00 am – 5:00 pm (EST)

www.dkgroup.com
www.forframersonly.com
©2010 D&K Group, Inc.

Expression® Finish Guard™ UV Specifications

Product/#			Roll Sizes		
Note: All rolls are now pierced					
GLOSS			CANVAS		
1371	41" x 50'	(1.04 x 15.2m)	H1671	41" x 50'	(1.04 x 15.2m)
SUEDE					
1381	41" x 50'	(1.04 x 15.2m)			
SATIN MATTE					
1306	41" x 50'	(1.04 x 15.2m)			


Expression® UV Accessories

Product/#	Sizes
Sponge Foam Overlay	
1322	51" x 8.5'
1309	42" x 8.5'


How To Use Finish Guard™ UV Laminating Films




Step 1
Warm the mounting press to 200-225°F. Position the print and mounting adhesive onto the substrate and tack in place.



Step 2
Peel back Finish Guard's release paper backing about 1" to expose the adhesive. Position the film on the print and smooth into place: gradually peel off the remaining backing paper. The repositionable adhesive lets you easily remove ripples and creases, if necessary.



Step 3
Cover the assembled materials with a Sponge Foam Overlay and place inside a Release Folder. Insert materials face up into the press, close and wait 3 to 5 minutes for a mechanical press, 7 to 9 minutes for a vacuum press.



Step 4
Remove and place under a Expression® Weight to cool. Do not bend or flex until fully cooled.