



# Optistick™ Decal Laminate

Optistick™ Premium and Optistick™ Removable Heat Assist Decal Laminates are ideal for one pass decaling of prints. A crystal-clear polyester substrate is coated on one side with a low melt thermal adhesive (activates at 180° - 200°F) and an optically clear pressure sensitive acrylic adhesive on the reverse side. A single silicone treated moisture-stable release liner protects the permanent or removable pressure sensitive adhesive until application.



Thermal/PSA  
Adhesive

Release  
Liner

## Optistick™ Removable

Ideal for temporary graphics, Optistick™ Removable features a removable pressure sensitive adhesive that can be repositioned with ease.

## Optistick™ Premium

Low melt thermal polyester adhesive with permanent pressure sensitive adhesive protected by a polyester liner. Available in a 4 mil configuration with a release liner.



Decal Composition

### Pre-Coat Boards With Optistick™

- 1) Select a smooth, flat board such as Foamboard
- 2) Process the board and Optistick™ laminate through a cold laminator, adhering the side containing the pressure sensitive adhesive to the board while simultaneously removing the PSA liner.
- 3) You are now left with a pre-coated board featuring a low melt thermal adhesive that is ready to adhere to a print.

### Optistick™ Premium

Part #	Roll Size
OSP38200	38" x 200'
OSP41200	41" x 200'
OSP51200	51" x 200'
OSP54200	54" x 200'
OSP61200	61" x 200'

### Optistick™ Removable

Part #	Roll Size
OSR38200	38" x 200'
OSR41200	41" x 200'
OSR51200	51" x 200'
OSR54200	54" x 200'
OSR61200	61" x 200'



The above information is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. All material should be tested by purchaser to determine final suitability.

