Superkote 42 Industrial

School/Desktop Equipment

The SuperKote Laminator is versatile, operator-friendly and safe. This industrial machine accepts a broad range of laminating films – from 1.5 mil to 10 mil. Designed to handle today's oversized graphics, yet just the right size for all professional, everyday applications. The SuperKote Industrial Laminator is a heavy-duty, industrial strength machine capable of accepting board stock up to $\frac{1}{2}$ " in thickness. It is ideal for quick print shops, graphic houses and service bureaus and features a pressure sensitive waste rewind.



Independent upper & lower temperature control



Adjustable tension controls



Heavy-duty variable speed motor



High capacity forced air cooling fans enhance lamination quality

Key Features:

Accommodates substrates up to 1/2" thick.

- In-Line slitter- allows document trimming during lamination.
- Variable roller pressure accommodates a wide range of different film stocks.
- Spring-loaded adjustable pressure on laminating and pull rollers.
- Adjustable tension to assure controlled, smooth, even lamination.
- Independent upper & lower electronic temperature control with digital LED display.
- "Ready", "Wait" lights "Ready" indicates when the laminator has reached pre-set temperature.
- Heavy-duty 2" top-grade silicone rubber rollers.
- Heavy-duty chain & sprocket drive.
- Teflon Heat Shoe designed for easy cleaning and scratch-free lamination.
- □ Forward/Reverse Variable Speed (0-15 FPM)
- □ Waste rewind feature allows single side lamination of pressure sensitive films.
- □ Made in the U.S.A.

The above information is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. All material should be tested by purchaser to determine final suitability.



Technical Specifications

Working Width:	41″
Laminator Width:	51″
Height:	20"
Depth (with feed tray):	24"
Net Weight:	280 lbs.
Shipping Weight:	330 lbs.
Speed:	0-15 fpm
Maximum Temperature:	300° F
Maximum Aperture:	1/2"
Roller Diameter:	2 1/4" (3" core adapter kit available)
Air Requirements:	N/A
Electrical Requirements:	220 - 240 V

Available Options

Foot switch - Provides hands free operation for guiding materials during lamination. Footage Counter - Used to track laminating film usage.

> D&K Group Inc. 1795 Commerce Drive Elk Grove Village, IL, 60007 www.dkgroup.com

P: 800.632.2314 F: 847.956.8214

