

The Accu III - 3210 Cutter is available as a stand-alone unit or as part of a complete D&K laminating system. This cutter is also easily integrated into many other one sided laminating and finishing systems. An electronic eye sensor detects sheet underlaps and activates a flying knife blade system that cleanly separates prints without frayed edges. Installation is simple and doesn't require any tie-ins such as nuts, bolts, clamps, etc.



System 3210 With Inline Accu III Cutter

Technical Specifications

Dimensions:	52" W x 52" L x 40" H
Electrical:	120 VAC - 2 Wire Service + Ground 60 HZ; Single Phase 15 A
Air:	1 CFM @ 100 PSI with Storage Tank; 1/2 - 1 HP
Shipping Weight:	338 lbs.
Speed:	Up to 100 fpm
Min. Sheet Size:	8 1/2" x 11"
Max. Sheet Size:	31.5" x 40"
Min. Sheet Thickness:	80 lb. Text
Max. Sheet Thickness:	20 pt. Board



System 3210 With Inline Accu III Cutter



Made in the USA

The above information is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. All material should be tested by purchaser to determine final suitability.